

SMS G32

ACTIVE HIGH-PERFORMANCE
INFRASONIC SUBWOOFER



| | |
|--|--|
| Speaker type Loudspeaker | Custom-built 32" woofer, 16 cm voice coil, 90 mm linear excursion (world record), with AIA Speaker Management Technology Spezial gefertigter 82 cm Treiber, 90 mm linearer Hub (Weltrekord), 16 cm Schwingspule mit AIA Speaker Management Technologie |
| Passive Active | Active, built in DSP Amplifier Aktiv, eingebauter DSP Verstärker |
| Enclosure type Prinzip | Sealed Geschlossen |
| Cont./peak output Dauer-/Spitzenleistung | 120 dB cont. / 122dB peak (@ 25 Hz) |
| Frequency Range Frequenzbereich | 7 Hz - 65 Hz |
| Air volume displacement Bewege Luft in Litern | 16,6 L / in comparison 18" standard cinema subwoofer 1,1 L 16,6 L / zum Vergleich Standard 18" Kinosubwoofer 1,1 L |
| Directivity horizontal x vertical in Deg° | 360° |
| Output Power Leistung | 6.000 W |
| Power voltage range | 85 V - 265 V |
| Input sensivity, balanced input impedance | 2.7V (with gain 32dB), 10k |
| Analogue Input - Amplifier Analog-eingang - Verstärker | 1 x XLR balanced 1 x XLR symmetrisch |
| Analogue Ouput - Amplifier Analog-ausgang - Verstärker | 1 x XLR balanced 1 x XLR symmetrisch |
| Power connector Strom | Neutrik powerCON True 1 in-out |
| Network Switch Netzwerkanschluss | 2ports Ethernet switch for daisy chain |

| | |
|--|--|
| Controlling Steuerung | OCS Software control, auto discovery |
| Features Funktionen | Manual Room acoustics-correction, delay, phase, crossover, voicing preset, gain, input sensitivity Manuelle Raumakustikkorrektur, Frequenzweiche, Delay, Phase, |
| Protection features Schutzfunktionen | Turn-on transients, Over-heating, DC, RF, Short-circuit, mismatched loads, ICL™, PMS™ |
| Enclosure Gehäuse | Internally braced birch ply Innenverstrebtres Birkensterrholz |
| Width Breite | 37,40" 950 mm |
| Hight Höhe | 47,24" 1200 mm |
| Hight with feet Höhe | 48,23" 1225 mm |
| Depth with plug Tiefe mit Stecker | 21,65" 550 mm |
| Depth without grill Tiefe ohne Abdeckung | 21,65" 550 mm |
| Weight Gewicht | 352,74 lbs 160 kg |
| Finish Oberfläche | PU structural paint Robuster Strukturlack schwarz |
| Custom colour options Farbvarianten | Piano lacquer (12 layers): colour of choice, matt or other finishes upon request, color of choice Echter Klavierlack (12 Schichten): Farbe nach Wahl, Mattlack: Farbe nach Wahl, weitere Oberflächen auf Anfrage |
| Shape customization Sondergröße | Upon request Auf Anfrage |
| Mounting Montage | Floor standing with feet |

Technical modifications subject to change without further notice | Technische Änderungen vorbehalten